

Indicative Maximum Loads (KG) at various full jib lengths – see spec sheets for precise information

Max jib length	Max height under hook	Max Load (KG)	Single/phase	10M	12M	14M	16M	18M	20M	22M	24M	26M	28M	30M	32M	34M	36M	38M	40M	42M	44M	45M	50m
Self-erecting cranes																							
24 M – CBR24/IGO18	19.1 M	1,800	S/3	1,800	1,660	1,375	1,165	1,005	880	780	700												
26 M – CBR26/IGO21	19.3 M	1,800	S/3	1,800	1,800	1,490	1,265	1,095	965	860	775	700											
30 M – IGO32	22 M	4,000	3	4,000	3,215	2,640	2,230	2,000	1,700	1,520	1,375	1,310	1,200	1,100									
32 M – CBR32/IGO36	22 M	4,000	3	4,000	3,460	2,845	2,410	2,080	1,940	1,730	1,485	1,350	1,200	1,190	1,100								
35 M – CBR36/HD40A	22 M	4,000	3	4,000	3,695	3,060	2,600	2,255	1,985	1,770	1,595	1,445	1,320	1,215	1,120	1,040	1,000						
40 M – CBR40/IGO 50	23.2 M	4,000	3	4,000	4,000	3,665	3,105	2,690	2,365	2,000	2,000	1,920	1,755	1,550	1,435	1,290	1,250	1,210	1,100				
City cranes																							
40 M – CTT51/A2	20-40 M	2,000	S/3	2,000	2,000	2,000	2,000	2,000	2,000	1,900	1,800	1,600	1,500	1,400	1,350	1,250	1,100	1,050	1,000				
45 M – MC68B	20-40 M	3,000	3	3,000	3,000	3,000	3,000	3,000	3,000	2,450	2,200	2,000	1,850	1,700	1,550	1,450	1,400	1,260	1,200	1,100	1,040	1,000	
52 M – MCT88	20-40 M	5,000	3	5,000	5,000	5,000	3,900	3,400	3,200	3,000	2,500	2,500	2,300	2,150	2,000	1,900	1,700	1,600	1,550	1,450	1,300	1,200	1,100